



GE Protimeter *Protimeter Mini*



For general purpose measurement applications in wood, buildings, caravans and other structures.

Choose the Protimeter Mini for your general moisture measurement applications.

The Protimeter Mini moisture meter has been the instrument of choice for thousands of users across the world for over 30 years. The enduring popularity and success of these instruments is attributable to their versatility, simple design, robust construction and ease of use.



Typical users include:

- Surveyors for routine moisture inspections of buildings
- Contract painters and decorators
- Joiners and carpenters
- Wood product manufacturers and traders
- Caravan manufacturers and traders

Building Surveying



The Protimeter Mini is ideal for assessing the moisture condition in buildings. A colour coded scale enables the user to assess the moisture level of wood and masonry at a glance. The numerical values represent the actual percent moisture content of wood (%MC) and the wood moisture equivalent (WME) of masonry and other materials.


Hence, the Mini can be used to determine if the fabric of a building are in a dry, borderline or damp condition.

Optional Deep Wall Probes can be used with the Mini to measure the moisture level at depth in a wall, irrespective of the surface condition. Deep Wall Probes are very useful accessories when investigating the cause of moisture problems within buildings.



Quality Control Applications

The Protimeter Mini is a precision instrument suitable for a wide range of quality control applications on construction sites, for manufacturers and for storage environments. Painters and decorators use the meter to assess if plasterwork is sufficiently dry for painting. Manufacturers of wooden products such as furniture, roof trusses and pallets use the Mini for checking the moisture content of timber as delivered, and through the manufacturing process.



When taking readings in awkward positions, the Mini can be used with the moisture probe and lead, supplied as standard with the instrument. The optional Protimeter Hammer Electrode can also be used with the Mini for determining moisture gradients in wood.

Specifications

Part no.	BLD2000
Weight, including batteries (g)	150
Dimensions (mm)	180 x 28 x 49
Display	LED
Batteries	LR6 (AA) x2
Measurement range % WME	6 to 90

The information in this leaflet is given in good faith. But since the method of use of the meters and the interpretation of the readings are beyond the control of the manufacturers, they cannot accept responsibility for any loss, consequential or otherwise, resulting from or involving the use of the meters. The specification of the product(s) may be changed without prior notice. Protimeter and Protimeter Mini are Registered Trade Marks. © GE Protimeter plc March 2005



GE Infrastructure Sensing - Protimeter

c/o Panametrics Ltd, Shannon Industrial Estate
Shannon Airport, County Clare, Ireland
Tel: 00 353 61 470200 Fax: 00 353 61 471359
protimeter@ge.com www.protimeter.com